

HYDRODAM NIGERIA LIMITED

RC443986

CONSTRUCTION, LAND RECLAIMATION, DREDGING ROADS, BRIGDES CONSTRUCTION,
BUILDING DESIGNS, ENGINEERING & CONSULTANCY.
10 BORI ROAD RUMUIBEKWE ESTATE PORT HARCOURT RIVERS STATE
TEL: 08033366149

Email: <u>hydrodamlimited@gmail.com</u> Website: www.hydrodamgroup.com



Н	YDRO GRACE	1270	1270
	ELLICOT 1270 ''DRAGON®'' FERHEAD DREDG	English	Metric
GENERAL	Discharge pipe x Suction pipe	18" x 18"	450 x 450
	Dredging Depth, maximum	50'	15 M
	Length, Overall, with Ladder raised	98'-6"	29.7 m
	Length, Hull	68'	20.7 m

	Width, Hull, including side pontoons	30'	9.1 m
	Depth, Hull	4'-6"	1.4 m
	Number of Pontoons (tanks)	3	3
	Plate Thickness of center pontoon	1/4" & 5/16"	6 & 8
	Dry Weight	221,000 lbs	100,244 kg
	Hull Draft, not including spuds	2'-10"	.86 m
	Fuel Capacity	10,600 gallons	40,125 liters
	Swing Width, @ minimum Dredging Depth	125'	39.9 m
	Swing Width, @ maximum Dredging Depth	92'	27.9 m
	Main Engine (Caterpillar)	C32	C-32
ENGINES	Power	1000 HP	746 KW
	Rating	Marine Tier 3	Marine Tier 3
	Cooling	Heat Exchanger	Heat Exchanger
	Auxiliary Engine (Caterpillar)	C-9	C-9
	Power	350 HP	261 KW
	Rating	Tier 3	Tier 3
	Cooling	Radiator	Radiator
TOTAL INSTALLED POWER	Not including optional Genset	1350 HP	1007 KW
CUTTER DRIVE	Power at Cutter Shaft	155 HP	116 KW
	Cutter Speed	29 - 42 RPM	29-42 RPM
	Cutter Diameter	54"	1372
	Cutting Force	<mark>7,</mark> 991 lbs	3,625 kg
SPUDS	Diameter	18"	457
SPUDS	Length	<mark>65'</mark>	19.7 m
PRODUCTION		<mark>up to</mark> 600	up to 500
	Capacity Range of Pumping System	cubic yards per hour	cubic meters per hour